


CORRUFLEX/BUNA/AS



Extremely flexible PVC/NBR suction and discharge hose with static wire to discharge static electricity.

Marking:  Corruflex / Buna / AS - Inside diameter mm

Norm	EN ISO 1307:2008	Color tube	Black
Vacuum	0,90 bar	Compound cover	NBR/PVC
Min. temperature	-30 °C	Cover	Slightly corrugated
Max. temperature	+65 °C	Color cover	Black
Compound tube	NBR/PVC	Reinforcements	Rigid PVC spiral, Static wire
Construction tube	Smooth	Color spiral	Blue

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	WP at 20°C (bar)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
4466050000	51,0	4,5	60,0	2,0	153	0,960	50
4466075000	76,0	5,5	87,0	2,0	228	1,600	50
4466100000	102,0	7,0	116,0	2,0	306	2,700	50
4466150000	152,0	8,0	168,0	2,0	456	4,750	20

Application: Suitable for transport of (industrial) water, dung and mineral oils under medium heavy working conditions. The hose is produced from a high quality PVC/NBR blend with a specially developed, very innovative, unique "mushroom shaped" hard PVC spiral, which makes this hose very flexible and fairly smooth on the outside. The flexibility and durability in combination with the fairly smooth exterior of the hose ensures that it is frequently used for (industrial) cleaning activities, agricultural machines, municipal works, sewage treatment, grease separators and emptying of tanks where very high demands are placed on these products.

Remark:

- Cutted length possible
- We recommend using cord for hose assembly
- Regarding the overpressure we would like to refer to the guidelines for the right use of the hoses which are mentioned on our website

We recommend assembly with

5510
Kamlok couplings



5721
Perrot couplings



6200
Super clamps

