


Antiabrasive polyurethane and thermoplastic rubber compound hose with polyester yarn reinforcement and polyurethane liner for pneumatic tools in general, airbrushes and water based paint sprayers.



- 
SMOOTH SURFACE

- 
FLEXIBILITY

- 
ABRASION RESISTANCE

- 
TEMPERATURE RANGE
-15 °c 60 °c

- 
CHEMICAL RESISTANCE
PU Table

- 
CRUSHING RESISTANCE

- 
FOR FOOD

Suitable for contact with foodstuff according to the declaration of conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	working press. at 40° bar	working press. at 60° bar	bursting press. at 23° bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
6	1/4	6	10	20	17	15	60	20	2	65	24x52°	100	In stock
8	5/16	8	12	20	17	15	60	22	2	85	18x52°	60	In stock
8	5/16	8	13.5	20	17	15	60	30	2.7	120	18x50°	60	On demand
10	3/8	10	15	20	17	15	60	38	2.5	130	24x52°	50	In stock
13	1/2	13	19	20	17	15	60	65	3	195	24x54°	30	In stock
16	5/8	16	22.5	20	17	15	60	60	3.2	250	24x54°	25	In stock