

- CONTENT
- AIR & WATER
- AIR CONDITION
- BRAKE
- BREATHING
- BUNKER
- CHEMICAL
- COOLANT
- FOOD
- FUEL
- GAS
- HYDRAULIC
- MATERIAL HANDLING
- OIL
- OIL COOLING
- POWERSTEERING
- PVC
- STEAM
- WELDING & GAS
- INDEX

Codan 1225 Air / Water Hose



Codan 1225 -

Black water hose for use where a flexible, hard-wearing, weather and ozone-resistant hose is required. Peak temp. 160 C. We recommend crimp on fittings. Please contact Codan for further information.

Type nr. 1225

Application: Air / Water Hose

Standard Length: 50 metres

Working Temperature: -30°C to 140°C

Inside: EPDM

Colour: Black

Reinforcement: High Strength Synthetic Textile Yarns

Outside: EPDM

Colour: Black

Standards:

Std. branding: -

| Inside dia. (mm) | Outside dia. (mm) | Working Pressure BAR | Burst Pressure BAR | Bend Radius (mm) | Weight (g/m) | Product code |
|------------------|-------------------|----------------------|--------------------|------------------|--------------|--------------|
| 6,3 | 13,0 | 20 | 60 | 40 | 152 | 1225016000 |
| 9,5 | 16,5 | 20 | 60 | 50 | 230 | 1225010000 |
| 12,7 | 21,5 | 20 | 60 | 65 | 360 | 1225013000 |
| 19,0 | 27,0 | 20 | 60 | 105 | 450 | 1225019000 |
| 25,0 | 35,0 | 20 | 60 | 145 | 800 | 1225025000 |

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanised Rubber Products).

The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.

- CONTENT
- AIR & WATER
- AIR CONDITION
- BRAKE
- BREATHING
- BUNKER
- CHEMICAL
- COOLANT
- FOOD
- FUEL
- GAS
- HYDRAULIC
- MATERIAL HANDLING
- OIL
- OIL COOLING
- POWERSTEERING
- PVC
- STEAM
- WELDING & GAS
- INDEX

Codan 1227 Air / Water Hose



Codan 1227 -

Green water hose for use where a flexible, hard-wearing, weather and ozone-resistant hose is required. Peak temp. 160 C. We recommend crimp on fittings. Please contact Codan for further information.

Type nr. 1227

Application: Air / Water Hose

Standard Length: 50 metres

Working Temperature: -30°C to 140°C

Inside: EPDM

Colour: Black

Reinforcement: High Strength Synthetic Textile Yarns

Outside: EPDM

Colour: Green

Standards:

Std. branding: -

| Inside dia. (mm) | Outside dia. (mm) | Working Pressure BAR | Burst Pressure BAR | Bend Radius (mm) | Weight (g/m) | Product code |
|------------------|-------------------|----------------------|--------------------|------------------|--------------|--------------|
| 9,5 | 16,5 | 20 | 60 | 50 | 230 | 1227010000 |
| 12,7 | 21,5 | 20 | 60 | 65 | 360 | 1227013000 |
| 19,0 | 27,0 | 20 | 60 | 105 | 450 | 1227019000 |
| 25,0 | 35,0 | 20 | 60 | 145 | 800 | 1227025000 |

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanised Rubber Products).

The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.

- CONTENT
- AIR & WATER
- AIR CONDITION
- BRAKE
- BREATHING
- BUNKER
- CHEMICAL
- COOLANT
- FOOD
- FUEL
- GAS
- HYDRAULIC
- MATERIAL HANDLING
- OIL
- OIL COOLING
- POWERSTEERING
- PVC
- STEAM
- WELDING & GAS
- INDEX

Codan 1228 Air / Water Hose



Codan 1228 -

Blue water hose for use where a flexible, hard-wearing, weather and ozone-resistant hose is required. Peak temp. 160 C. We recommend crimp on fittings. Please contact Codan for further information.

Type nr. 1228
Application: Air / Water Hose
Standard Length: 50 metres
Working Temperature: -30°C to 140°C
Inside: EPDM
Colour: Black
Reinforcement: High Strength Synthetic Textile Yarns
Outside: EPDM
Colour: Blue
Standards:
Std. branding: -

| Inside dia. (mm) | Outside dia. (mm) | Working Pressure BAR | Burst Pressure BAR | Bend Radius (mm) | Weight (g/m) | Product code |
|------------------|-------------------|----------------------|--------------------|------------------|--------------|--------------|
| 6,3 | 13,0 | 20 | 60 | 40 | 152 | 1228016000 |
| 9,5 | 16,5 | 20 | 60 | 50 | 230 | 1228010000 |
| 12,7 | 21,5 | 20 | 60 | 65 | 360 | 1228013000 |
| 19,0 | 27,0 | 20 | 60 | 105 | 450 | 1228019000 |
| 25,0 | 35,0 | 20 | 60 | 145 | 800 | 1228025000 |

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanised Rubber Products).

The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.

- CONTENT
- AIR & WATER
- AIR CONDITION
- BRAKE
- BREATHING
- BUNKER
- CHEMICAL
- COOLANT
- FOOD
- FUEL
- GAS
- HYDRAULIC
- MATERIAL HANDLING
- OIL
- OIL COOLING
- POWERSTEERING
- PVC
- STEAM
- WELDING & GAS
- INDEX

Codan 1229 Air / Water Hose



Codan 1229 -

Red water hose for use where a flexible, hard-wearing, weather and ozone-resistant hose is required. Peak temp. 160 C. We recommend crimp on fittings. Please contact Codan for further information.

Type nr. 1229

Application: Air / Water Hose

Standard Length: 50 metres

Working Temperature: -30°C to 140°C

Inside: EPDM

Colour: Black

Reinforcement: High Strength Synthetic Textile Yarns

Outside: EPDM

Colour: Red

Standards:

Std. branding: -

| Inside dia. (mm) | Outside dia. (mm) | Working Pressure BAR | Burst Pressure BAR | Bend Radius (mm) | Weight (g/m) | Product code |
|------------------|-------------------|----------------------|--------------------|------------------|--------------|--------------|
| 6,3 | 13,0 | 20 | 60 | 40 | 152 | 1229016000 |
| 9,5 | 16,6 | 20 | 60 | 50 | 230 | 1229010000 |
| 12,7 | 21,5 | 20 | 60 | 65 | 360 | 1229013000 |
| 19,0 | 27,0 | 20 | 60 | 105 | 450 | 1229019000 |
| 25,0 | 35,0 | 20 | 60 | 145 | 800 | 1229025000 |

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanised Rubber Products).

The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.

- CONTENT
- AIR & WATER
- AIR CONDITION
- BRAKE
- BREATHING
- BUNKER
- CHEMICAL
- COOLANT
- FOOD
- FUEL
- GAS
- HYDRAULIC
- MATERIAL HANDLING
- OIL
- OIL COOLING
- POWERSTEERING
- PVC
- STEAM
- WELDING & GAS
- INDEX

Codan 1231 Air / Water Hose



Codan 1231 - ISO 1403: 1995

Black, industrial-quality water hose for use in all types of industrial flushing, cleaning, etc. Hard-wearing surface that also has excellent weather and ozone resistance.

Please contact Codan for further information.

Type nr. 1231

Application: Air / Water Hose

Standard Length: 40 metres

Working Temperature: -30°C to 100°C

Inside: EPDM

Colour: Black

Reinforcement: Polyester

Outside: EPDM

Colour: Black

Standards: ISO 1403: 1995

Std. branding: -

| Inside dia. (mm) | Outside dia. (mm) | Working Pressure BAR | Burst Pressure BAR | Bend Radius (mm) | Weight (g/m) | Product code |
|------------------|-------------------|----------------------|--------------------|------------------|--------------|--------------|
| 51,0 | 61,0 | 10 | 30 | - | 1.360 | 1231051000 |
| 63,0 | 76,0 | 10 | 30 | - | 2.100 | 1231063000 |
| 76,0 | 90,0 | 10 | 30 | - | 2.740 | 1231076000 |