


# LOCK-ON PLUS



-size	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	mm/Hg	kg/100m	REF.
-4	6	1/4	0.47	11.9	300	2.1	1200	8.4	45	710	13	LOLA+04
-6	10	3/8	0.63	15.9	300	2.1	1200	8.4	75	710	16	LOLA+06
-8	12	1/2	0.77	19.6	300	2.1	1200	8.4	80	710	23	LOLA+08
-10	16	5/8	0.94	23.9	300	2.1	1200	8.4	115	710	30	LOLA+10
-12	19	3/4	1.06	26.9	300	2.1	1200	8.4	135	380	36	LOLA+12
-4	6	1/4	0.47	11.9	300	2.1	1200	8.4	45	710	13	LOLB+04
-6	10	3/8	0.63	15.9	300	2.1	1200	8.4	75	710	16	LOLB+06
-8	12	1/2	0.77	19.6	300	2.1	1200	8.4	80	710	23	LOLB+08
-10	16	5/8	0.94	23.9	300	2.1	1200	8.4	115	710	30	LOLB+10
-12	19	3/4	1.06	26.9	300	2.1	1200	8.4	135	380	36	LOLB+12
-4	6	1/4	0.47	11.9	300	2.1	1200	8.4	45	710	13	LOLC+04
-6	10	3/8	0.63	15.9	300	2.1	1200	8.4	75	710	16	LOLC+06
-8	12	1/2	0.77	19.6	300	2.1	1200	8.4	80	710	23	LOLC+08
-10	16	5/8	0.94	23.9	300	2.1	1200	8.4	115	710	30	LOLC+10
-12	19	3/4	1.06	26.9	300	2.1	1200	8.4	135	380	36	LOLC+12
-4	6	1/4	0.47	11.9	300	2.1	1200	8.4	45	710	13	LOLG+04
-6	10	3/8	0.63	15.9	300	2.1	1200	8.4	75	710	16	LOLG+06
-8	12	1/2	0.77	19.6	300	2.1	1200	8.4	80	710	23	LOLG+08
-10	16	5/8	0.94	23.9	300	2.1	1200	8.4	115	710	30	LOLG+10
-12	19	3/4	1.06	26.9	300	2.1	1200	8.4	135	380	36	LOLG+12
-4	6	1/4	0.47	11.9	300	2.1	1200	8.4	45	710	13	LOLR+04
-6	10	3/8	0.63	15.9	300	2.1	1200	8.4	75	710	16	LOLR+06
-8	12	1/2	0.77	19.6	300	2.1	1200	8.4	80	710	23	LOLR+08
-10	16	5/8	0.94	23.9	300	2.1	1200	8.4	115	710	30	LOLR+10
-12	19	3/4	1.06	26.9	300	2.1	1200	8.4	135	380	36	LOLR+12

**LOCK-ON PLUS**

<b>RECOMMENDED FOR</b>	Petroleum-based hydraulic oils, antifreeze solutions, water, hot lubricating oils and air. Suitable for low pressure cleaning and pneumatic systems, return lines and low pressure lines. Lock-On Plus hose and couplings are not recommended for pressure surge applications or critical applications.
<b>COMPOSITION</b>	NBR (Nitrile) based.
<b>REINFORCEMENT</b>	One fibre braid.
<b>COUPLER</b>	NBR/PVC based.
<b>TEMPERATURE RANGE</b>	-40°C to +100°C constant and +121°C intermittent. For water emulsions, etc. see page 86.
<b>STANDARDS</b>	Gates proprietary.
<b>COUPLINGS</b>	Lock-On Plus reusable couplings.
<b>CHARACTERISTICS/BENEFITS</b>	Available in 5 colours for easy colour coding. Easy to assemble.

A = black

B = blue

C = grey

G = green

R = red

