

CHARACTERISTICS

- Continuous working temperature : from -60°C to +250°C
- Peaks over 1000°C
- Good resistance to :
 - o Presence of flames
 - o Projection of metals or melting glass
 - o Occasional very high temperature
 - o Projection of vapour
- Excellent flexibility at low temperatures
- Slight swelling can be caused by hydrocarbons
- Good resistance to UV
- Asbestos free
- Self-extinguishing
- Watertight

COLOURS AND PACKAGINGS

- Manufactured diameters : From 4 to 45 mm
- Standard colour : Brick red
- Standard packagings : Bobbins or rolls

STANDARDS*

- Compliant with directive RoHS 2002/95/CE
- NF EN 60695-2 -10 (05-2001)
- NF EN 60695-2 -11 (07-2001)
- NF EN 60684-1 (10-2003)
- NF EN 60684-2 (01-1998) modified by NF EN 60684-2/A1 (12/2003), NF EN 60684-2/A2 (05/2006)
- NF EN (CEI) 60684-3 sheets 400 to 402 (02/2003)

APPLICATIONS

Iron and steel industry, foundries, glassworks, petrochemicals, shipbuildings, railways, aeronautics, ...

Inner diameter (mm)	Tolerance inner diameter (± mm)	Wall thickness (mm)
4	0.5	2
6	0.5	2
8	0.5	2
10	0.5	2
12	0.5	2
14	0.5	2
16	1.0	2
18	1.0	2
20	1.0	2
22	1.0	2
25	1.0	2
28	1.0	2
30	1.0	2
32	1.0	2
35	1.0	2
38	1.0	2
40	1.0	2
42	1.0	2
45	1.0	2



* Our products pass all or parts of requirements for the above-mentioned standards. The technical informations written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.