



Espiroflex

FÁBRICA DE TUBERÍA FLEXIBLE

C/. VIC S/N POL. IND. LA FLORIDA 08130 STA. PERPETUA DE LA MOGODA

TEL: 935602400 FAX : 935602626 Web: <http://www.espiroflex.com> E-mail : info@espiroflex.com

TRANSAIR

CHARACTERISTICS

Tube made from flexible PVC with rigid spiral, practically non deformable and anti-choke.

The inner surface is smooth while the exterior one is corrugated.

Great flexibility (bending radius equal to interior diameter) and lightness.

Resistant to impacts, atmospheric agents, to smoke and to a wide range of chemical products.

Temperature range between -15°C and 65°C

USAGE

Aspiration and impulsion of fumes, shavings, seeds, textile fibres, etc, where protection from fire is necessary.

Industrial aspiration and ventilation

TECHINICAL DATA

Ø INT. mm	WALL mm	WEIGH T g/m	VACUUM m H ₂ O	BENDING RADIUS mm	Ø INT. mm	WALL mm	WEIGHT g/m	VACUU M m H ₂ O	BENDING RADIUS mm
15	2,1	100	5	15	80	4,5	780	4	80
19	2,1	115	5	19	90	4,5	830	4	90
20	2,5	120	5	20	102	5,0	980	4	100
25	2,6	170	5	25	110	5,2	1150	4	110
26	2,6	200	5	26	120	5,5	1200	4	120
30	2,8	210	5	30	125	5,5	1250	4	125
32	3,0	218	5	32	130	5,5	1300	4	130
34	3,0	235	5	34	140	5,5	1500	4	140
35	3,1	240	5	35	150	6,0	1700	4	150
38	3,1	260	5	38	160	6,0	1920	4	160
40	3,2	280	4	40	180	6,5	2200	4	180
45	3,5	410	4	45	200	7,0	2400	4	200
50	3,5	450	4	50	250	7,0	3000	4	250
55	3,5	490	4	55	300	8,0	3600	4	300
60	4,0	540	4	60					
65	4,0	590	4	65					
70	4,2	640	4	70					
75	4,5	690	4	75					

01-12-2010