GMS HADICE

Čestné prohlášení:

Certifikát 2.1 pro výrobek:

Kód produktu: 10327



Obchodní název a popis:

AEROTEC BLACK PU98SH

Polyuretanová hadice na vzduch nebo plyny (-15/+80°C)

&

TUBE PU CALIBRÉ 98 ShA

Výrobce: Hozelock Tricoflex

- Pracovní teplota: **-15°C až +80°C**
- Pracovní tlak: **8 až 10 Bar**
- Bezpečnost: **3 : 1**
- Použití produktu: **PU kalibrovaná, jednovrstvá hadička pro dopravu stlačeného vzduchu a vzduchové rozvody v pneumatice.**
- Vlastnosti: **98° ShA, hladký vnitřní i vnější povrch**
- Materiál vnitřní: **PU - polyuretan**
- Materiál vnější: **PU – polyuretan (jednovrstvá hadice)**
- Výztuha: **Kruhový tvar**
- Spirála: **--**
- Médium: **Tlakový vzduch, oleje i kapaliny**
- Norma: **Bez ftalátů**
- Barva vnitřní: **Černá**
- Barva vnější: **Černá**
- Zkrácená poznámka: **Všechny parametry uvedené v tabulce jsou při 20°C. Vyšší teplota má za následek snížení provozního tlaku.**

GMS hadice, s.r.o. | Nádražní 491 Lanškroun 56301 | IČO: 25954113 DIČ: CZ25954113 | tel.: 465 323 825 e-mail: info@gms.cz | www.gms.cz

GMS HADICE

Originální katalogový list :

TUBE PU CALIBRÉ POLYURETHANE

30 | 24 bar

+80 / - 15 °C



1 Blue, red, black or translucent polyurethane

High precision calibrated polyurethane tube (hardness 98 shA).

Mono layer design in flexible translucent or coloured polyurethane. Smooth inner and outer surfaces.

APPLICATIONS

Pneumatic controls, transfer of fluids and liquids under pressure: fuel and lubricants, lacquers and some solvents (please consult us)

SECTORS OF ACTIVITY

Used for automatic functions on all types of machines: concerns numerous industries using assembly machines, packaging lines... laboratories

Marking TUBE PU CALIBRE Ø inn x Ø out [Batch number]

ADVANTAGES

The CALIBRATED PU TUBE is remarkable for its flexibility and lightweight. An active calibration process ensures an excellent dimensional accuracy. It has good general chemical resistance, especially for oils, hydrocarbons and some solvents. Its low friction factor is provided by the very smooth texture of the outer and inner surfaces. Varied colours help to identify the different networks easily. Packaging in a cardboard cassette facilitates storage.

CONNECTORS

Shut off connectors. P.C.L. type connectors.

CHEMICAL RESISTANCE

See table pages 102 to 105 column C.

Coils in carton boxes

mm	mm	+/- mm	mm	+/- mm	g/m	bar	bar	mm	Black 25 m	Black 100 m
4	6	+/-0,1	1	+/-0,12	19	30	10	15	070804	070810
5.5	8	+/-0,1	1.25	+/-0,12	32	27	9	20	070865	070878
6	8	+/-0,1	1	+/-0,12	26.8	27	9	22	071144	071155
7.5	10	+/-0,15	1.25	+/-0,15	41.3	24	8	30	072425	

Za velkoobchod GMS hadice, s.r.o.

Vypracoval:
Fabián Karel,
produktový manažer

Schválil:
Jan Tovtík,
ředitel společnosti

GMS HADICE
KVALITA SKLADEM

GMS hadice s. r. o.
Nádražní 491
563 01 Lanškroun
IČ: 25954113
DIČ: CZ25954113
tel.: 465 323 825
www.gms.cz

V Lanškrouně dne 19.09.2024