



MANUFACTURING & MACHINE TOOLS

Air and water

Water discharge under pressure on industrial or urban sites.

Advantages

- Sturdy hose.
- Good resistance to abrasion thanks to wall thickness.

Technical description

Inner tube: SBR for ID≤25mm, EPDM for ID>25mm, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, red, smooth for ID≤25mm, fabric impression for ID>25mm.

Temperature range: -25°C to +70°C.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (●) or min. order m
13.0	4.0	21.0	10	30	78	0.36	40	5503031	●
16.0	4.0	24.0	10	30	96	0.43	20	5503404	●
							40	5503040	●
19.0	4.5	28.0	10	30	115	0.56	20	5503405	●
							40	5503032	●
25.0	5.0	35.0	10	30	150	0.80	20	5503406	●
							40	5503033	●
32.0	5.5	43.0	10	30	200	0.90	40	5503034	●
38.0	6.0	50.0	10	30	210	1.00	40	5503035	●
50.0	7.0	65.0	10	30	400	1.60	40	5503036	●

Tolerance on length: ±1% (ISO 1307 Standard).



Digital version

