



TECHNICAL DATA SHEET

RIF.: S.T. CALORTEC 165 BB

REV. 0

HOSE: CALORTEC 165 BB

CODE: 532730161-01623112

APPLICATION: Delivery hose for hot water at +95°C

INNER TUBE: Black, smooth EPDM rubber compound

REINFORCEMENT: High strength synthetic plies

COVER: Black, smooth, cloth Impression EPDM rubber compound , abrasion, ozone and weather resistant

LENGTH: 40 m rolls

BRANDING: Embossed "CALORTEC 165 BB"

WORKING TEMPERATURE: -40° + 165°C

TECHNICAL DETAILS

INTERNAL DIAMETER (mm):	19	25																	
TOLERANCES ON INTERNAL ID (± mm):	0,6	0,8																	
OUTER DIAMETER (mm):	31	38																	
TOLERANCES ON OUTER ID. (± mm):	0,8	1,0																	
WORKING PRESSURE (bar):	6	6																	
BURST PRESSURE (bar):	> 60	> 60																	
BENDING RADIUS (mm):	100	150																	
WEIGHT (Kg/m)	0,58	0,73																	

Dimensional Tolerances in conformity to ISO 1307

Date: 10/09/2014

Signature : Chiara Bordini

Tubi gomma Torino