

# CALORSTAR R /210°C

STEEL WIRE REINFORCEMENT STEAM HOSE 17 BAR - BS 5342 -2A



## APPLICATION

Delivery hose for high pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry

## TUBE

Black, smooth, EPM rubber compound

## REINFORCEMENT

High tensile strength steel reinforcements

## COVER

Red, smooth, pin pricked, cloth impression EPM rubber compound, abrasion, ozone and weather resistant

## WORKING TEMPERATURE

-40°F +410°F peaks 450°F  
-40°C +210°C picchi 232°C

## SPECIFICATIONS

BS 5342:85 TYPE 2 CLASS A

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	25	1	0.53	17	255	170	2550	120	40/61
16	5/8	28	1 7/64	0.60	17	255	170	2550	155	40/61
19	3/4	32	1 1/4	0.76	17	255	170	2550	185	40/61
25	1	38	1 1/2	0.98	17	255	170	2550	240	40/61
32	1 1/4	46	1 13/16	1.29	17	255	170	2550	330	40/61
38	1 1/2	54	2 1/8	1.76	17	255	170	2550	390	40/61
51	2	67	2 41/64	2.18	17	255	170	2550	520	40/61
63	2 1/2	83	3 15/64	3.40	17	255	170	2550	640	40/61
76	3	96	3 25/32	4.35	17	255	170	2550	745	40/61
102	4	124	4 7/8	7.00	17	255	170	2550	990	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

**CALORSTAR**

W.P. 17 BAR 210°C BS 5342 type 2A

DRAIN AFTER USE

ITALY

**tubi gomma torino**