

Čestné prohlášení:

Certifikát 2.1 pro výrobek:

Kód produktu: 10318



Obchodní název a popis:

DRINKTEC CITERDIAL 6/SPL

Tlaková a sací hadice pro potravin. produkty, mléko a alkohol do 96%

&

CITERDIAL

Výrobce: TRELLEBORG

- Pracovní teplota: **-30°C až +80°C**
- Pracovní tlak: **6 Bar**
- Bezpečnost: **3 : 1**
- Použití produktu: **Hadice pro cisterny, přepravu, vykládací prostory a stacionární zařízení, zpracovatelské a plnicí zařízení k sání a výtlačku mléka a alkoholu do 96% s výjimkou tučných potravin a olejů.**
- Materiál vnitřní: **NR**
- Materiál vnější: **NR odolné proti klimatickým vlivům a oděrům**
- Výztuha: **Syntetický proplet**
- Spirála: **Ocelová**
- Médium: **Kapalně potraviny, mléko, pivo, víno a alkohol do 96 %**
- Norma výrobku: **1935/2004 CE; 2023/2006; FDA 21 CFR 177.2600; BfR doporučení XXI kat. 2.; bez ftalátů**
- Barva vnitřní: **Bílá**
- Barva vnější: **Modrá**
- Zkrácená poznámka: **Hadice je extrémně flexibilní bez zalomení a není nedoporučena k přepravě tuků a olejů. Všechny příslušné migrační zkoušky byly provedeny a potvrzeny jako vyhovující Francouzským institutem Poitiers (IANESCO). Sterilizace parou při teplotách do +110 °C po dobu max. 10-ti minut. Uvedené parametry v tabulce platí při teplotě 20°C.**

Originální katalogový list:

CITERDIAL

PROCESSING EQUIPMENT

Food industry/Transfer

For milk handling: tanker lorries for milk collection and transport, dairy unloading bays and stationary equipment, processing and filling plant.
Also for transfer of other liquid foodstuffs such as wine, beer, cider, fruit juice, vinegar and alcohol up to 96%, with exception of fatty foodstuffs and oils.

Advantages

- Extremely flexible to accept the smallest bending radius without kinking.
- Smooth, seamless, white tube that does not propagate bacterial growth and complies with the most stringent French, European and American requirements for foodstuff handling.
- Unaffected by changes in temperature, the advantage of rubber over PVC.
- Resistant to cleaning with most common detergents (see our cleaning guideline for details) or with steam at max. 110°C during 10 minutes max.
- Non-marking, abrasion resistant cover.
- Contains no phthalate.



Technical description

Inner tube: food grade quality NR, white, smooth.
Reinforcement: synthetic textile with embedded steel helix.
Cover: weather and abrasion resistant NR, blue, fabric impression.

Temperature range: -30°C to +80°C.

Standard/Approval:

EU regulations No. 1935/2004, 2023/2006.

FDA regulation No. 21 CFR 177.2600.

German legislation: BfR recommendation XXI cat. 2.

French legislation.

All relevant migrations tests (France and FDA) were performed by the French institute of Potiers (IANESCO) and confirmed compliant.

Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (●) or min. order m		
25.0	-0/+1	36.0	±1.0	6	18	0.9	50	0.70	20	0122924	●
									40	0127209	●
32.0	-0/+1	43.0	±1.0	6	18	0.9	64	0.82	13.3	0070653	□
									40	0123639	●
38.0	-0/+1	49.0	±1.0	6	18	0.9	76	1.14	13.3	0060068	●
									40	0060069	●
40.0	-0/+1	51.0	±1.0	6	18	0.9	80	1.27	13.3	0060072	●
									40	0060074	●
45.0	-0/+1	56.0	±1.0	6	18	0.9	90	1.38	20	0060141	□
									40	0060142	●
51.0	-0/+1	63.0	±1.5	6	18	0.9	102	1.79	13.3	0060777	●
									15	0060776	●
									40	0060775	●
53.0	-0/+1	65.0	±1.5	6	18	0.9	106	1.85	13.3	0060079	□
									40	0060082	●
60.0	-0/+1	72.0	±1.5	6	18	0.9	120	2.09	13.3	0060083	□
									40	0060085	●
63.0	-0/+1	75.0	±1.5	6	18	0.9	126	2.17	13.3	0060086	●
									15	0060087	●
									40	0060089	●
70.0	-0/+1	83.5	±1.5	6	18	0.9	140	2.62	13.3	0060090	●
									40	0060092	●
76.0	-0/+1	89.5	±1.5	6	18	0.9	152	3.03	13.3	0060788	●
									40	0060787	●
100.0	-0/+1	114.0	±1.5	6	18	0.9	350	3.67	20	0060099	●
									40	0060071	●
125.0	-0/+1	145.5	±1.5	6	18	0.9	450	6.05	10	0060202	●
									20	0060203	●
150.0	-0/+1	171.5	±1.5	6	18	0.9	530	7.02	10	0060204	□
									20	0060205	●

Za velkoobchod GMS hadice, s.r.o.

Vypracoval:

Fabián Karel,
produktový manažer



Schválil:

Jan Tovtík,
ředitel společnosti



V Lanškrouně dne 2.1.2024



GMS hadice s. r. o.
Nádražní 491
563 01 Lanškroun
IČ: 25954113
DIČ: CZ25954113
tel.: 465 323 825
www.gms.cz

LANŠKROUN
OLOMOUC
OSTRAVA
PARDUBICE
PRAHA
ZLÍN

GMS hadice, s.r.o.

Nádražní 491
Lanškroun 56301

IČO: 25995413
DIČ: CZ 25995113

tel.: 465 323 825
e-mail: info@gms.cz

www.gms.cz