ESPIROFLEX
FABRICA DE TUBERIA FLEXIBLE

DECLARATION OF CONFORMITY

PRODUCT:	**TRANSMETAL PF**
CODE:	**173500XX**

REV:	3
DATE:	27/05/2026

It is declared that the products with the title code:

This product is made with a metallic spiral coated by two layers of plasticized PVC without phthalates.

This products are produced according to the following community legislations:

Regulation (CE) nº 1935/2004
Regulation (CE) nº 1895/2005
Regulation (CE) nº 2023/2006
Regulation (UE) nº 10/2011 and subsequent updates

The product pass the test of the GML (global migration limit), using OM2 test condictions, according to the current normative, UNE-EN 1186-3.

PROPERTY	SIMULANT	REQUIREMENT [mg/dm²]	AVERAGE VALUE [mg/dm²]	RESULT
Global migration	B	< 10	0,6	OK
Global migration	D1	< 10	5,7	OK

It's according to the organoleptics requirements, established in the (CE) 1935/2004 regulation.

Restricted substances and components:

The product has the following restricted substances included in the annexes I and II of the (UE) 10/2011 regulation, from the current law.

Chemical name	Nº MCA	Nº of Ref.	Nº CAS	Restriction SML [mg/kg]
Bis(2-ethylhexyl) terephthalate	798	92200	6422-86-2	60
ESBO, Soybean oil, epoxidized	532	88640	8013-07-8	60
Oxidized polyethylene waxes	811	80077	68441-17-8	60
Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	433	68320	2082-79-3	6
Zinc salts	(*)	-	-	5
Vynil Chloride	127	26050	75-01-4	ND (1 mg/kgin the final product)

(*) Annex II EU Regulation 10/2011

C/ VIC S/N (ESQUINA C/CADAQUÉS) - POL. IND. LA FLORIDA
08130 SANTA PERPETUA DE LA MOGODA
TEL: 935602400 // FAX : 935602626
www.espiroflex.com
info@espiroflex.com

ESPIROFLEX
FABRICA DE TUBERIA FLEXIBLE

SML test conditions:

1) Restricted substances

Simulants B and D1 repeated use OM2 test conditions:

Terms of use:

This product can be used in contact with foods with lipophilic properties wich are able to extract lipophilic substances.

The simulant B, will be used with foods with a pH lower than 4,5. The simulant D1 will be used with alcoholic foods with an alcoholic graduation higher than 20 % and aqueous emulsions oil.

Long storage at room temperature or lower, including heating up to 70ºC for a maximum of 2 hours, or the heating up to 100 ºC for a maximum of 15 minutes.

The ratio between the food contact surface used to determine the conformity of the sample has been 1,5/150 dm^2/ml.

It is the responsibility of the final customer to sterilize this product before use.

The simulants and test conditions have been selected in accordance with Regulation (EU) 10/2011 Annex III Table 1 and Annex V Table I and II and successive updates.

Santa Perpètua de la Mogoda, a 27/05/2025

Materials manager

C/ VIC S/N (ESQUINA C/CADAQUÉS) - POL. IND. LA FLORIDA
08130 SANTA PERPETUA DE LA MOGODA
TEL: 935602400 // FAX : 935602626
www.espiroflex.com
info@espiroflex.com