



to.  
**GMS VELKOOBCHOD S.R.O.**  
NADRAZNI 491  
563 01 LANSKROUN CZ

**Certificate of Conformity according to EN 10204:Aug.95 point 2.1.**

We confirm to you that our hose type **ABR VOLGA NN** has got the following features ( according to your order specifications ) :

- Hose name : **ABR VOLGA NN**
- Art.nr. : 1255282; 1034464; 1358308.
- Dimension : 76X92mm; 80x94mm; 102x119mm.
- Weight : 3,20 kg/m; 3,0 kg/m; 4,9kg/m.

Application: hardwall hose used for the suction and delivery of dry cement, sand, gravel, etc.  
Standards: abrasion loss of the tube according to ISO 4649: 50 +/- 5mm<sup>3</sup>.  
Temperature: from -30°C (-22°F) to +70°C (+158°F).

Construction

Tube: black, smooth, antistatic SBR/NR rubber which withstands the passage of abrasive materials.  
Reinforcement: high strength synthetic cord, steel helix wire and antistatic copper wire. Cover: black, smooth (wrapped finish), EPDM rubber, weathering and ozone resistant.

- Working pressure : 10 bar S.F. 3:1 (standard application)
- Temperature range : -30°C bis +70°C
- Compound : tube cover
- Elastomer : NR/SBR EPDM

Max. Production length: 120 mt

Cervarese S. Croce, March 7<sup>th</sup> 2022

**IVG Colbachini SpA**  
Ing. Simone Capetta  
Product Engineer