

MULTI MASTER



mm	mm	MPa	MPa	mm	kg/100m	REF.
6	13.0	2.0	8.0	50	14	MULTI MASTER - 6mm
8	15.0	2.0	8.0	50	18	MULTI MASTER - 8mm
10	17.0	2.0	8.0	75	21	MULTI MASTER - 10mm
13	21.0	2.0	8.0	100	29	MULTI MASTER - 13mm
16	25.0	2.0	8.0	125	40	MULTI MASTER - 16mm
19	29.0	2.0	8.0	125	53	MULTI MASTER - 19mm
25	37.0	2.0	8.0	200	83	MULTI MASTER - 25mm
32	44.0	2.0	7.0	250	99	MULTI MASTER - 32mm
38	50.0	2.0	7.0	300	115	MULTI MASTER - 38mm

RECOMMENDED FOR

Premium multipurpose hose for air and water applications requiring maximum flexibility in any industry including mining, construction, agriculture, vehicle repair and in-plant operations. Also suitable for light agricultural spraying, such as dilute solutions of herbicides.

TUBE

EPDM based.

REINFORCEMENT

Textile layers, spiralled.

COVER

EPDM based.

TEMPERATURE RANGE

-40°C to +100°C constant and +110°C intermittent.

STANDARDS

Gates proprietary.

CHARACTERISTICS/BENEFITS

Electrical conductive: $R < 10^6 \text{ Ohm}$.

Burst pressure $> 3.15 \times$ working pressure.

Outstanding resistance to heat and ozone.