

MULTIKLER



MANUFACTURING & MACHINE TOOLS



Multipurpose oil

APPLICATIONS

Pressure service line for benzene, toluene and xylene based paints, lacquer, varnish and certain chemicals.

Also for industrial paint spray equipment.

ADVANTAGES

- † Hose cover resistant both to abrasion and to corrosive chemicals.
- † Free from silicone.
- † Antistatic tube.

TECHNICAL DESCRIPTION

Inner tube: solvent paints resistant NBR, black, smooth.

Reinforcement: synthetic textile.


Cover: oil and weather resistant NBR/PVC, green, smooth.

Temperature range: -20°C to +100°C.

Electrical properties: antistatic tube, $R < 10^6 \Omega/m$.

COUPLINGS/FITTINGS

Special paint hose couplings are recommended.





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.14	40	0064197	2680
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.14	80	0064198	2640
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.14	120	0064199	2640
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.17	20	0064201	∅
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.17	40	0064202	∅
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.17	80	0064203	2640
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.17	120	0064204	∅
10.0 ±0.5	3.75	17.5 ±0.6	20	60	90	0.24	20	0064207	∅
10.0 ±0.5	3.75	17.5 ±0.6	20	60	90	0.24	40	0064208	∅
10.0 ±0.5	3.75	17.5 ±0.6	20	60	90	0.24	80	0064209	2240
10.0 ±0.5	3.75	17.5 ±0.6	20	60	90	0.24	120	0064210	2280
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.28	20	0064211	∅
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.28	40	0064212	∅
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.28	80	0064213	1520
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.28	120	0064214	1440
16.0 ±0.7	4.5	25.0 ±0.8	20	60	130	0.38	20	0064215	∅
16.0 ±0.7	4.5	25.0 ±0.8	20	60	130	0.38	40	0064216	∅
16.0 ±0.7	4.5	25.0 ±0.8	20	60	130	0.38	80	0064217	1360
16.0 ±0.7	4.5	25.0 ±0.8	20	60	130	0.38	120	0064218	1320

Tolerance on length: ±1% (ISO 1307 Standard).

∅ Upon availability.

Digital version





MANUFACTURING & MACHINE TOOLS

Multipurpose oil

Pressure service line for benzene, toluene and xylene based paints, lacquer, varnish and certain chemicals.
Also for industrial paint spray equipment.

Advantages

- Hose cover resistant both to abrasion and to corrosive chemicals.
- Free from silicone.
- Antistatic tube.

Technical description

Inner tube: solvent paints resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, green, smooth.

Temperature range: -20°C to +100°C.

Electrical properties: antistatic tube, $R < 10^6 \Omega/m$.

Couplings/Fittings

Special paint hose couplings are recommended.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (●) or min. order m
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.14	40	0064197	2680
							80	0064198	2640
							120	0064199	2640
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.17	20	0064201	□
							40	0064202	●
							80	0064203	2640
10.0 ±0.5	3.75	17.5 ±0.6	20	60	90	0.24	120	0064204	●
							20	0064207	●
							40	0064208	●
13.0 ±0.6	4.0	21.0 ±0.7	20	60	110	0.28	80	0064209	2240
							120	0064210	2280
							20	0064211	□
16.0 ±0.7	4.5	25.0 ±0.8	20	60	130	0.38	40	0064212	●
							80	0064213	1520
							120	0064214	1440
16.0 ±0.7	4.5	25.0 ±0.8	20	60	130	0.38	20	0064215	□
							40	0064216	●
							80	0064217	1360
							120	0064218	1320

□ Upon availability.

Tolerance on length: ±1% (ISO 1307 Standard).



Digital version

