



## OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of  
NSF/ANSI 51 - Food Equipment Materials

This is the Official Listing recorded on April 1, 2020.

**ITG SRL**  
**Via Fusline, 36**  
**25036 Palazzolo S/O (BS)**  
**Italy**  
**39 03 074 03534**

**Facility: Palazzolo S/O (BS), Italy**

Trade Designation	Color	Type of food	Maximum Temperature of Use in °F
Silicone Seals and O-rings for Food Zone			
O-Rings(1)(2)A <sup>[1]</sup>	Natural	All food contact types	212°
O-Rings(1)(2)B <sup>[1]</sup>	Grey	All food contact types	212°
Gaskets(1)(2)(3)(4)( <sup>[2]</sup> 5)(6)A	Natural	All food contact types	212°
Gaskets(1)(2)(3)(4)( <sup>[2]</sup> 5)(6)B	Grey	All food contact types	212°
FKM Seals and O-rings for Food Zone			
O-Rings(1)(2)C <sup>[3]</sup>	Green	All food contact types	212°
Gaskets(1)(2)(3)(4)( <sup>[4]</sup> 5)(6)D	Green	All food contact types	212°
HOSEFLON® PTFE Tubing for Food Zone			
HOSEFLON	Transparent White	All food contact types	500°

- [1] (1) Up to 3 numbers for internal diameter (from 0,5 mm to 10000 mm).  
(2) Up to 4 digits for cord, including decimals (from 0.5 mm to 200.0) mm.
- [2] (1) Up to 3 possible numbers for width (from 0,05 mm to 10000 mm).  
Square or rectangular gaskets.  
(2) Up to 3 possible numbers for length (from 0,05 mm to 10000 mm).  
Square or rectangular gaskets.  
(3) Up to 2 possible numbers for height (from 0,05 mm to 1000 mm).  
Square or rectangular gaskets.  
(4) Up to 3 possible numbers for External Diameter (from 0,05 mm  
to 10000 mm). Only for circular gaskets.  
(5) Up to 2 possible numbers for Internal Diameter (from 0,05 mm  
to 10000 mm). Only for circular gaskets.  
(6) Up to 2 possible numbers for height (from 0,05 mm to 1000 mm).  
Only for circular gaskets.
- [3] (1) Up to 3 numbers for internal diameter (from 1 mm to 440 mm).  
(2) Up to 4 digits for cord, including decimals (from 0.5 mm to 13.0) mm.
- [4] (1) Up to 3 possible numbers for width (from 0,5 mm to 200 mm).  
Square or rectangular gaskets.  
(2) Up to 3 possible numbers for length (from 0,5 mm to 200 mm).  
Square or rectangular gaskets.  
(3) Up to 2 possible numbers for height (from 2mm to 90mm). Square  
or rectangular gaskets.  
(4) Up to 3 possible numbers for External Diameter (from 2mm to 100

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



- 
- mm). Only for circular gaskets.
- (5) Up to 2 possible numbers for Internal Diameter (from 2mm to 80 mm). Only for circular gaskets.
  - (6) Up to 2 possible numbers for height (from 2mm to 60 mm). Only for circular gaskets.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.

2 of 2