



CHEMIREX /10

FKM DELIVERY HOSE FOR CHEMICAL PRODUCTS



APPLICATION

Delivery hose for aggressive chemical products, acids at high concentration. For deeper information, please check the chemical resistance table at the end of the catalog

TUBE

Black, smooth, FKM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression ${\bf CR}$ rubber compound, resistant to chemical products, oils, ozone and weather

WORKING TEMPERATURE

-31°F +212°F

-35°C +180°C

		8		4	(22 22
ID mm inch		0D mm inch		WEIGHT	WP bar psi		BP bar psi		COIL LENGTH
mm 6	1/4	16	5/8	kg/m 0.27	10	psi 150	40	600	20/40
8	5/16	18	45/64	0.32	10	150	40	600	20/40
10	3/8	20	25/32	0.38	10	150	40	600	40
13	1/2	23	29/32	0.45	10	150	40	600	40
16	5/8	26	1 5/16	0.53	10	150	40	600	40
19	3/4	29	1 9/64	0.60	10	150	40	600	40
20	25/32	30	1 3/16	0.63	10	150	40	600	40
25	1	35	1 3/8	0.75	10	150	40	600	40
30	1 3/16	42	1 21/32	1.07	10	150	40	600	40
32	1 1/4	44	1 47/64	1.15	10	150	40	600	40
35	1 3/8	47	1 27/32	1.25	10	150	40	600	40
38	1 1/2	50	1 31/32	1.33	10	150	40	600	40
40	1 37/64	54	2 1/8	1.65	10	150	40	600	40
51	2	65	2 9/16	2.10	10	150	40	600	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING









ITALY

