GMS HADICE

Čestné prohlášení:

Certifikát 2.1 pro výrobek:

Kód produktu: 30243



Obchodní název a popis:

KAMLOK SS ZÁSLEPKA DP

Nerezová záslepka rychlospojky

&

Dust plugs

Výrobce: LUDECKE

- Pracovní teplota: **-40°C až +95°C**
- Pracovní tlak: **16 Bar**
- Použití produktu: **Kamlok - rychlospojkový systém pro všeobecné použití v průmyslu, zemědělství a cisternové dopravě.**
- Funkce: **Rychlospojka s adaptérem se utahují na principu 2 vaček, které zajišťují výbornou těsnost a vysokou pevnost spoje.** Velkou výhodou systému je libovolná vzájemná poloha adaptéru a rychlospojky při jejich spojování.
- Materiál produktu: **Nerez AISI 316 (1.4401)**
- Materiál těsnění: **--**
- Médium: **Voda, oleje, emulze i abraziva**
- Norma: **AISI 316/1.4401, Evropská norma EN 14420-7, USA podle A-A-59326A**
- Barva: **Stříbrná**
- Zkrácená poznámka: **Rychlospojky doporučujeme upínat k hadicím sponami GBS nebo systémem nekonečného pásu Bandimex.**

GMS hadice, s.r.o. | Nádražní 491 Lanškroun 56301 | IČO: 25954113 DIČ: CZ25954113 | tel.: 465 323 825 e-mail: info@gms.cz | www.gms.cz

Originální katalogový list:

Kamlok Quick Couplings

DIN EN 14 420-7, MIL-C-27487 made of Stainless Steel 1.4401

- High-quality, robust couplings according to US-Mil.-Standard (MIL-C-27487) or DIN EN 14 420-7 (former DIN 2828) made of stainless steel 1.4401
- Interchangeable with common worldwide used types
- Female threads with thread sealing ring made of PTFE
- Seals made of NBR, Hypalon, EPDM and FKM, as well as handles and spare parts
- Couplings always come with handle securing and safety clips (steel zinc-plated)
- Universal coupling for aggressive media (depending on mixture/ concentration) in chemical and petrochemical industry, steel and food industry, medical technology, shipbuilding or agriculture
- Current information about standards for DIN EN 14 420-7 (page 335)

Materials

- Female part, male part, handle: Stainless Steel 1.4401
- Seals: NBR

Max. Working Pressure	Temperature	Thread	Norm	Media	
PN 16 bar	-40°C – +95°C	ISO 228 / DIN EN 10226	MIL-C-27487/ DIN EN 14 420-7	Different	1



Dust Plugs (DIN EN 14 420-7 Form DP)

L	Type-Size	ID	DN	Weight	Type No.
36	50	24.3	15	73	50-DP-SS
39	75	32.1	20	93	75-DP-SS
46	100	36.7	25	139	100-DP-SS
55	125	45.5	32	260	125-DP-SS
57	150	53.4	40	335	150-DP-SS
60	200	63	50	441	200-DP-SS
66	250	75.8	65	657	250-DP-SS
66	300	91.5	80	804	300-DP-SS
68	400	119.5	100	1525	400-DP-SS

Za velkoobchod GMS hadice, s.r.o.

Vypracoval:
Fabián Karel,
produktový manažer

Schválil:
Jan Tovtík,
ředitel společnosti

V Lanškrouně dne 12.5.2025

GMS HADICE
KVALITA SKLADEM

GMS hadice s. r. o.
Nádražní 491
563 01 Lanškroun
IČ: 25954113
DIČ: CZ25954113
tel.: 465 323 825
www.gms.cz