PETROCRAFT D /20 EN 1825 TYPE C

DELIVERY HOSE AIRCRAFT GROUND REFUELLING - EN 1825 TYPE C



APPLICATION
Delivery hose for aircraft ground refuelling. Fuels with aromatic content up to 50%

TUBE
Black, smooth, conductive (R≤10^6 Ohm) **NBR** rubber compound

REINFORCEMENT
High strength synthetic plies

COVER
Black, smooth, fire proof and conductive (R≤10^6 Ohm), cloth impression **CR** rubber compound, resistant to chemical products, ozone and weather

WORKING TEMPERATURE
-22°F +158°F
-30°C +70°C

SPECIFICATIONS
EN 1825 TYPE C / TRbF

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
19	3/4	29	1 9/64	0.52	20	300	80	1200	113	40/61
25	1	38	1 1/2	0.84	20	300	80	1200	150	40/61
32	1 1/4	45	1 25/32	1.00	20	300	80	1200	200	40/61
38	1 1/2	51	2	1.16	20	300	80	1200	230	40/61
51	2	65	2 9/16	1.70	20	300	80	1200	305	40/61
63.5	2 1/2	79	3 7/64	2.06	20	300	80	1200	390	40/61
76	3	92	3 5/8	2.56	20	300	80	1200	460	40/61
102	4	120	4 23/32	3.73	20	300	80	1200	610	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING



Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42
Ph: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it

Copyright © TUBI GOMMA TORINO S.p.a. - All rights reserved. The texts and images are owned by Tubi Gomma Torino S.p.A. Even partial reproduction of the catalog is prohibited. In the continuous search for technical and functional improvements, Tubi Gomma Torino S.p.A reserves the right to make changes to its products, which can be made without notice.