GMS HADICE

Čestné prohlášení, návod na obsluhu:

Certifikát 2.1 pro výrobek:

Kód produktu: 10509



Obchodní název a popis:

SPIROTEC PVC BARCELONA

Tlaková a sací hadice pro fekálie a kapaliny, -20°C až +60°C

& Espiroflex, S.A.

TRANSFORT SUPERELASTIC ROJO

Výrobce: Espiroflex Španělsko

- Pracovní teplota: **-25°C až +60°C**
- Bezpečnost: **3 : 1**
- Použití produktu: **Univerzální plastová hadice zemědělské potřeby.**
- Materiál vnitřní: **PVC**
- Materiál vnější: **PVC, červená s modrou spirálou**
- Výztuha: **Plastový tvrzený drát**
- Médium: **Voda a kapaliny, chemické produkty, granuláty, osiva a obiloviny**
- Norma: **EN ISO 3994**
- Vlastnosti: **Hadice na sání a výtlak kapalin a vody, práce při nízkých teplotách, hadice pro čištění kanalizací, určena zvláště pro cisternové a fekální vozy.**
- **Zkrácená Uvedené parametry v tabulce platí při teplotě 20°C.**

- Tabulka výrobce na další straně (k dispozici pouze ve Španělském jazyku výrobce)

Vypracoval:
Fabián Karel,
produktový manažer

GMS hadice, s.r.o. | Nádražní 491 Lanškroun 56301 | IČO: 25954113 DIČ: CZ25954113 | tel.: 465 323 825 e-mail: info@gms.cz | www.gms.cz

Espiroflex
FÁBRICA DE TUBERÍA FLEXIBLE

TRANSFORT SUPERELASTIC ROJO

CHARACTERISTICS

Tube made by co-extrusion of vinyl components, according the European Quality Norm UNE EN ISO 3994. Reinforced inside with a non plasticized PVC spiral, practically non deformable and anti-choke, which provides it a great consistency. The spiral is embedded by super elastic, red, flexible material, resistant to low temperatures, and it is covered on top by a spiral blue band, made also from flexible, low temperature resistant material.
The tube is smooth inside, which prevents from the formation of sediments and facilitates the sterilization of them.
Non toxic.
Resistant to the atmospheric agents and to several chemical products
The recommended using temperature is within –25ºC and 60ºC.

USAGE

Draining of cesspools, sewers. Industrial sprinkling. Suction and impulsion of liquid manure and chemical products. Pneumatic transport of seed and cereal. Transporting of powder and granules. Due to its great flexibility, it is recommended for using on tank cars.

DATOS TECNICOS

$Ø_{INT}$ (mm)	$Ø_{EXT}$ (mm)	PESO (g/m)	Presión de servicio (bar)	Radio curvatura (mm)
25	33,8	500	7	100
32	40,8	600	6	130
38	46,8	600	6	150
40	49	700	6	160
45	55	700	6	180
51	62	900	5	200
60	71,2	1100	5	240
63	75	1300	5	240
70	83	1600	4	280
76	89	2000	4	300
80	93	2100	4	320
90	103,4	2600	4	360
102	116,8	2900	3	400
105	119,8	3000	3	420
110	125	3100	3	440
120	136	3600	3	480
127	143,6	3900	3	510
130	147	4100	3	520
152	170	5000	2	610
160	178,8	5600	2	640
202	218	10000	2	800

Za velkoobchod GMS hadice, s.r.o.

Schválil:
Jan Tovtík,
ředitel společnosti

GMS HADICE
KVALITA SKLADEM

GMS hadice s. r. o.
Nádražní 491
563 01 Lanškroun
IČ: 25954113
DIČ: CZ25954113
tel.: 465 323 825
www.gms.cz

V Lanškrouně dne 25.8.2026