

Čestné prohlášení:

**Certifikát 2.1 pro výrobek:**

**Kód produktu: 10860**



Obchodní název a popis:

**DRINKTEC ALIKLER 10/SPL**

**Tlaková a sací flexibilní hadice pro potravin. produkty a alkohol do 95% ALIKLER G2  
&  
ALIKLER G2**

**Výrobce: TRELLEBORG**

- Pracovní teplota: **-30°C až +100°C (pára 130 °C)**
- Pracovní tlak: **10 Bar**
- Bezpečnost: **3 : 1**
- Použití produktu: **Tlaková a sací hadice pro mléko, tekuté potraviny a alkohol do 95 %.**
- Materiál vnitřní: **NBR (bílé)**
- Materiál vnější: **NBR/PVC– odolné proti olejům, oděrům a klimatickým vlivům**
- Výztuha: **Syntetický proplet**
- Spirála: **Ocelová**
- Médium: **Tekuté potraviny, mošt, mléko, olej, pivo, víno a alkohol do 95 %**
- Norma výrobku: **EU 1935/2004, 2023/2006, FDA 21 CFR 177.2600, BfR XXI kat. 2, francouzská legislativa, neobsahuje ftaláty**
- Barva vnitřní: **Bílá**
- Barva vnější: **Modrá s bílým popisem**
- Zkrácená poznámka: **Sanitace se provádí parou při teplotách do +130°C po dobu max. 30 minut. K dispozici jsou také speciálně navržené koncovky.**

**Uvedené parametry v tabulce platí při teplotě 20°C.**

Originální katalogový list:



### Food industry/Transfer

Suction and discharge of liquid foodstuffs such as wine, beer, milk, oil, fats, cider, fruit juice and alcohol up to 95%.  
For unloading bays, processing and filling plants and liquid foodstuff tankers.  
Additional air line on road tankers carrying bulk powdered products (not compressor line) at temperatures up to +120°C.

### Advantages

- Improved flexibility, very easy to handle.
- A smooth, seamless, white, multipurpose food grade tube that does not propagate bacterial growth.
- Excellent resistance to kinking.
- Changes in temperature have little effect due to the qualities of the rubber compound.
- Resistant to cleaning with most common detergents (see our cleaning guideline for details) or with steam at max. 130°C.
- Non-marking, abrasion-resistant cover.
- Contains no phthalate.

### Technical description

**Inner tube:** food grade quality oil resistant NBR, white, smooth.  
**Reinforcement:** synthetic textile with embedded steel helix.  
**Cover:** oil and weather resistant NBR/PVC, blue, fabric impression.

**Temperature range:** -30°C to +100°C.

### Standard/Approval:

EU regulations No. 1935/2004, 2023/2006.  
FDA regulation No. 21 CFR 177.2600.  
German legislation: BfR recommendation XXI cat. 2.  
French legislation.  
All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

### Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (●) or min. order m		
25.0	-0+1	37.0	±1.0	10	30	0.9	40	0.92	20	5513357	●
									40	5513358	●
32.0	-0+1	44.0	±1.0	10	30	0.9	55	1.10	20	5513359	●
									40	5513360	●
38.0	-0+1	50.0	±1.0	10	30	0.9	65	1.26	20	5513361	●
									40	5513362	●
45.0	-0+1	57.0	±1.0	10	30	0.9	90	1.45	20	5513363	120
									40	5513364	120
50.0	-0+1	62.0	±1.5	10	30	0.9	100	1.77	20	5513365	●
									40	5513366	●
									20	5513383	∞
53.0	-0+1	65.0	±1.5	10	30	0.9	110	1.86	20	5513367	●
									40	5513368	●
									20	5513369	●
63.0	-0+1	76.0	±1.5	10	30	0.9	135	2.24	20	5513370	●
									40	5513371	●
70.0	-0+1	84.5	±1.5	10	30	0.9	175	3.07	20	5513372	120
									40	5513373	120
75.0	-0+1	89.5	±1.5	10	30	0.9	190	3.29	20	5513374	●
									40	5513375	●
									20	5513385	∞
76.0	-0+1	90.5	±1.5	10	30	0.9	200	3.45	20	5513386	●
									40	5513387	●
									20	5513388	∞
89.0	-0+1	104.5	±1.5	10	30	0.9	275	3.89	20	5513376	80
									40	5513377	80
100.0	-0+1	115.5	±1.5	10	30	0.9	400	4.40	20	5513378	●
									40	5513379	●
125.0	-0+1	145.5	±2.0	10	30	0.9	600	6.74	10	5513380	●
									20	5513381	●
150.0	-0+1	171.5	±2.0	10	30	0.9	700	8.35	10	5513382	●
									20	5513383	●

Za velkoobchod GMS hadice, s.r.o.

Vypracoval:

Fabián Karel,  
produktový manažer



Schválil:

Jan Tovtík,  
ředitel společnosti



V Lanškrouně dne 5.1.2024



**GMS hadice s. r. o.**  
Nádražní 491  
563 01 Lanškroun  
IČ: 25954113  
DIČ: CZ25954113  
tel.: 465 323 825  
www.gms.cz

**LANŠKROUN  
OLOMOUČ  
OSTRAVA  
PARDUBICE  
PRAHA  
ZLÍN**

**GMS hadice, s.r.o.**

**Nádražní 491  
Lanškroun 56301**

**IČO: 25995413  
DIČ: CZ 25995113**

**tel.: 465 323 825  
e-mail: info@gms.cz**

**www.gms.cz**