

- CONTENT
- AIR & WATER
- AIR CONDITION
- BRAKE
- BREATHING
- BUNKER
- CHEMICAL
- COOLANT
- FOOD
- FUEL
- GAS
- HYDRAULIC
- MATERIAL HANDLING
- OIL
- OIL COOLING
- POWERSTEERING
- PVC
- STEAM
- WELDING & GAS
- INDEX

Codan 2823 Welding & Gas Hose



Codan 2823 - EN ISO 3821:2019

Black, flexible dry-flow hose for argon and nitrogen. Mainly for use in industrial argon-welding applications.

Special butyl rubber developed to prevent moisture from permeating the hose and mixing with the medium.

A very strong, non-porous weld is thus achieved. Please contact Codan for further information.

Type nr. 2823

Application: Argon / nitrogen

Standard Length: 50 metres

Working Temperature: -25°C to 100°C

Inside: CIIR

Colour: Black

Reinforcement: Ester

Outside: CIIR

Colour: Black

Standards: EN ISO 3821:2019

Std. branding: CODAN DRY-FLOW® ARGON EN ISO 3821:2019 2 MPa (20BAR)

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
5,2	12,6	20	60	60	138	2823005000
6,3	13,9	20	60	63	150	2823006000
10,0	18,4	20	60	100	233	2823010000
15,0	24,0	20	60	150	341	2823015000