GMS HADICE

Čestné prohlášení:

Certifikát 2.1 pro výrobek:

Kód produktu: 10120



Obchodní název a popis:

PETROTEC FUB

Tlaková hadice pro benzíny, oleje, naftu a bionaftu,(-40/+100°C), 12 bar

&

FUB

Výrobce: SEMPERIT

- Pracovní teplota: **-40°C až +100°C (+120°)C**
- Bezpečnost: **4** : **1**
- Použití produktu: **Palivová hadice pro motorová vozidla**
- Materiál vnitřní: **NBR, černé a hladké**
- Materiál vnější: **Syntetická pryž odolná vůči i olejům, benzínům, výborná odolnost vůči abrazi a ozónu**
- Spirála: **Bez spirály**
- Výztuha: **Dvojitý oplet ze syntetických materiálů**
- Norma výrobku: **SAE J30R2 /(R6), EN 228:2017 (bezolovnatá paliva), EN 590:2017**
- Médium: **Benzíny, nafta B20, B100 - bionafta, B7, E5, E10, E85 a E100, oleje**
- Barva: **Černá**
- Zkrácená poznámka: **Hadice pro dopravu benzínů, nafty, bionafty (B100) a olejů. Hadice FUB není určena pro použití s leteckými palivy v leteckém průmyslu. Hadice splňuje a překračuje podmínky normy SAE J30R6.**

GMS hadice, s.r.o. | Nádražní 491 Lanškroun 56301 | IČO: 25995413 DIČ: CZ 25995113 | tel.: 465 323 825 e-mail: info@gms.cz | www.gms.cz

GMS HADICE

Originální katalogový list v anglickém jazyce:

SEMPERIT

FUB



Fuel/Oil - 12 bar

Application:
Suitable for the delivery of unleaded fuels (EN 228:2017) and diesel oils (EN 590:2017) for cars, trucks and tractors.

Suitable for the usage in engine compartments of trucks.

Feature:
Suitable for B100 (100% biodiesel = RME), B20, B7 (EN 590:2017), E5 (EN 228:2017), E10, E85 and E100.

The used liner fulfills RMA class A.

Standard/approval:
SAE J30R2 and SAE J30R6.

Notice:
Delivered coil can consist of several hose lengths.

Temperature range:
-40°C / +100°C, ambient temperature +120°C.

Safety factor:
4 : 1

Tube:
NBR, black, resistant to oil, smooth.

Reinforcement:
Textile spiral.

Cover:
Quality performance rubber, black, resistant to ozone and weather, resistant to oil, smooth.

Marking:
continuous colored marking, green letters:
"SEMPERIT (S) FUB 386 Kraftstoff/Fuel PN 12 bar ID SAE J30R2 / SAE J30R6 XQ/YYYY MADE IN EU //////".



Article number	Internal-Ø in		Wall width	External-Ø	Work. pressure	Number of inserts	Bending radius	Weight approx.	Coil length
	mm	inch	in mm	in mm	(max.) bar		(min.) in mm	kg/m	(max.) m
68031 0430	4,0		3,0	10,0	12	2	25	0,09	-
68031 0527	5,0	3/16	2,7	10,5	12	2	30	0,10	-
68031 0630	6,0	1/4	3,0	12,0	12	2	35	0,13	-
68031 0830	8,0	5/16	3,0	14,0	12	2	50	0,17	-
68031 0932	9,5	3/8	3,2	16,0	12	2	60	0,19	-
68031 1235	12,0		3,5	19,0	12	2	70	0,26	-

Za velkoobchod GMS hadice, s.r.o.
Vypracoval:
Fabián Karel,
produktovj manažer

Schválil:
Jan Tovtík,
ředitel společnosti

V Lanškrouně dne 20.10.2023

GMS HADICE
KVALITA SKLADEM

GMS hadice s. r. o.
Nádražní 491
563 01 Lanškroun
IČ: 25954113
DIČ: CZ25954113
tel.: 465 323 825
www.gms.cz