AERDEL /20

COMPRESSED AIR HOSE- HEAVY DUTY



APPLICATION

Delivery hose for compressed air suitable for heavy duty pneumatic tools in road constructions, railways works, tunneling and mining, etc

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **SBR**/**EPDM** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22°F +176°F
-30°C +80°C

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	23	29/32	0.37	20	300	60	900	40
16	5/8	26	1 5/16	0.43	20	300	60	900	40
19	3/4	30	1 3/16	0.58	20	300	60	900	40/61
25	1	37	1 29/64	0.80	20	300	60	900	40/61
32	1 1/4	44	1 47/64	1.00	20	300	60	900	40/61
35	1 3/8	48	1 57/64	1.25	20	300	60	900	40/61
38	1 1/2	52	2 15/32	1.45	20	300	60	900	40/61
40	1 37/64	54	2 1/8	1.58	20	300	60	900	40/61
51	2	67	2 41/64	2.10	20	300	60	900	40/61
51	2	69	3 23/32	2.30	20	300	60	900	40/61
63.5	2 1/2	80	3 5/32	2.55	20	300	60	900	40/61
76	3	94	3 45/64	3.40	20	300	60	900	40/61
102	4	120	4 23/32	3.95	20	300	60	900	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING



Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42
Ph: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it

Copyright © TUBI GOMMA TORINO S.p.a. - All rights reserved. The texts and images are owned by Tubi Gomma Torino S.p.A. Even partial reproduction of the catalog is prohibited. In the continuous search for technical and functional improvements, Tubi Gomma Torino S.p.A reserves the right to make changes to its products, which can be made without notice.